

Mechanical characteristics: 機械的性能

Total rotational angle 全迴轉角度	$300^{\circ} \pm 10^{\circ}$
Rotational torque 迴轉扭力	10~200 gf.cm
Rotation stopper strength 止迴轉強度	Outer shaft 4Kgf.cm Inner shaft 3Kgf.cm
Push pull strength 軸堆拉強度	push 4 kgf / pull 3kgf

Electrical characteristics: 電氣的性能

Total resistance 總阻值	10K Ω ~500K Ω
Total resistance tolerance 總阻值容許差	$\pm 20\%$
Rated power 定格電力	curve B:0.05W other curve B:0.025W
Max.operating voltage 最高使用電壓	curve B:50V AC other curve B:25V AC
Slide noise 滑動噪音	less than 100mV
Resistance taper 阻值線性	A, B, C
Residual resistance 殘留阻值	$R \geq 250K\Omega$ 0.1% max. of total resistance $250K\Omega > R > 10K\Omega$ 20 Ω max. $10K\Omega \geq R$ 10 Ω max.
Insulation resistance 絕緣抵抗	more than 100M at DC 250V
Gang error 相互偏差	-40dB to 0dB 3dB max.

Durability: 耐久的性能

Rotational life 迴轉壽命	10,000 cycles
-------------------------	---------------